5TH WHEEL UNHITCHING CHECKLIST FOR WILD THING

Park the Trailer then Check the Level of the Trailer Side to Side
Use Anderson Leveling Blocks (or similar) as needed to Level the Trailer Laterally (Side to Side)
Install X-Chocks and Lock with a Padlock
Chock both Wheels with Front and Back Chocks
Lower Truck Tailgate
Disconnect the 7 Pin Connection
Lower Landing Gear to Blocks until the Weight of the Trailer is off the Hitch & On the Landing Gear
Observe the Truck Bed Angle and Envision how it will move away from the Trailer,
Remove Cotter Pin on Hitch Arm and Remove Break-Away Cable
Move Hitch Arm to Open Position and Pin in Open Position with Cotter Pin
Slowly Pull Truck Forward watching to be sure the Weight Stays On the Landing Gear, Not the Hitch
Adjust Height of Trailer Nose if Truck Bed is Angling Upward when Pulling Away. Where's the Weight?
Once the trailer is Fully Unhitched from the Truck, Level Trailer Front to Back using Landing Gear
Lower Rear Stabilizers
Make desired connections:
Connect Water Hose to City Water. Always Use Water Pressure Regulator
Connect Sewer Hose always using a Sewer Hose Support
Turn OFF ALL the breakers on the Campsite Electrical Power Connection Box
Connect Electrical Cord to the Campsite Electrical Power Connection Box then Turn On the Breaker
Connect TV Cable Connection if applicable
Install the 5 th Wheel King Pin Lock